UNIVERSITY OF CAMBRIDGE INTERNATIONAL EXAMINATIONS

International General Certificate of Secondary Education

MARK SCHEME for the October/November 2009 question paper for the guidance of teachers

0625 PHYSICS

0625/31


Paper 31 (Extended Theory), maximum raw mark 80

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes must be read in conjunction with the question papers and the report on the examination.

CIE will not enter into discussions or correspondence in connection with these mark schemes.

CIE is publishing the mark schemes for the October/November 2009 question papers for most IGCSE, GCE Advanced Level and Advanced Subsidiary Level syllabuses and some Ordinary Level syllabuses.



Page 2	Page 2 Mark Scheme: Teachers' version		Paper
	IGCSE – October/November 2009	0625	31

NOTES ABOUT MARK SCHEME SYMBOLS AND OTHER MATTERS

B marks are independent marks, which do not depend on any other marks. For a B mark to be scored, the point to which it refers must actually be seen in the candidate's answer.

M marks are method marks upon which accuracy marks (A marks) later depend. For an M mark to be scored, the point to which it refers **must** be seen in a candidate's answer. If a candidate fails to score a particular M mark, then none of the dependent A marks can be scored.

C marks are compensatory method marks which can be scored even if the points to which they refer are not written down by the candidate, provided subsequent working gives evidence that they must have known it. e.g. if an equation carries a C mark and the candidate does not write down the actual equation but does correct working which shows he knew the equation, then the C mark is scored.

A marks are accuracy or answer marks which either depend on an M mark, or which are one of the ways which allow a C mark to be scored.

c.a.o. means "correct answer only".

e.c.f. means "error carried forward". This indicates that if a candidate has made an earlier mistake and has carried his incorrect value forward to subsequent stages of working, he may be given marks indicated by e.c.f. provided his subsequent working is correct, bearing in mind his earlier mistake. This prevents a candidate being penalised more than once for a particular mistake, but **only** applies to marks annotated "e.c.f."

e.e.o.o. means "each error or omission".

brackets () around words or units in the mark scheme are intended to indicate wording used to clarify the mark scheme, but the marks do not depend on seeing the words or units in brackets.

e.g. 10 (J) means that the mark is scored for 10, regardless of the unit given.

underlining indicates that this must be seen in the answer offered, or something very similar.

OR/or indicates alternative answers, any one of which is satisfactory for scoring the marks.

Spelling Be generous about spelling and use of English. If an answer can be understood to mean what we want, give credit.

Significant Answers are acceptable to any number of significant figures ≥ 2, except if specified otherwise, or if only 1 sig.fig. is appropriate.

Units It is expected that all final answers will have correct units. Deduct one unit penalty for each incorrect or missing unit, maximum 1 per question. No unit penalty if unit is missing from final answer but is shown correctly in the working. No unit penalty for incorrect answer.

Fractions These are only acceptable where specified.

Extras Ignore extras in answers if they are irrelevant; if they contradict an otherwise correct response or are forbidden by mark scheme, use right + wrong = 0

Page 3	Mark Scheme: Teachers' version	Syllabus	Paper
	IGCSE – October/November 2009	0625	31

Ignore Indicates that something which is not correct is disregarded and does not cause a right plus wrong penalty.

Not/NOT Indicates that an incorrect answer is not to be disregarded, but cancels another otherwise correct alternative offered by the candidate i.e. right plus wrong penalty applies.

Work which has been crossed out, but not replaced, should be marked as if it had not been crossed out.

	Page 4				Syllabus	Paper	,
			IGCSE – October/Novem	ber 2009	0625	31	
1	(a)	microme	ter OR screw gauge OR vernier s	cale NOT vernier	callipers	B1	
	(b)	2.73 mm				B1	
	(c)	not too ti take read use seve	t zero) trument on to paper) ght/use ratchet) any 3 ling of both scales) ral sheets) ading by no. of sheets)			B1 × 3	[5]
2	(a)	immerse	ng cylinder with liquid statue rom difference of readings from mea	asuring cylinder		B1 B1 B1	
		displacei immerse	ment can/equivalent/beaker, <u>filled to</u> statue volume displaced <u>with measuring c</u>		quid	(B1) (B1) (B1)	
	(b)		/ OR 600/65 n³ (minimum 2 s.f.) N.B. unit pena	alty applies		B1 B1	
		(For gold) (M =) V × D OR 65 × 19 (minimum 2 s.f.) N.B. unit pena	alty applies		(B1) (B1)	
		(For gold) (V =) M / D OR 600/19 (minimum 2 s.f.) N.B. unit pen	alty applies		(B1) (B1)	
			ed if justified by previous work in (a) n wrong values above	or (b) .		В1	[6]
3	(a)	5 points	correctly plotted ±½ small square –1	e.e.o.o. (ignore 0	,0)	B2	
	(b)	3 N one,	however identified OR 3 rd value C	OR 4 th value		B1	
	(c)	good stra	aight line through origin and candida	ite's remaining poil	nts	B1	
	(d)	_	ne / constant gradient y Hooke's Law			M1 A1	
		special c	ase: obeys Hooke's law because fo	rce ∝ extension or	wtte	B1	

Page 5		Mark Scheme: Teachers' version	Syllabus	Paper	
		IGCSE – October/November 2009	0625	31	
	· , • ·	ecomes non-linear / curves / bends eference to direction of curve or bend.		B1	
	OR per	e exceeded / reached proportional / elastic limit manently deformed or equiv OR staightened I have broken OR no longer elastic or wtte		B1	[8]
4	(a) in direct	ion of the force Do not accept forward on is own.		B1	
		s direction / causes acceleration / stops straight line moving circle / keeps path circular / pulls object into circle	tion / keeps object	B1	
	` ' ` '	600 N same as his 1. accept 600 N if no value given in (c) (i)	1.	B1 B1	
	(ii) ma 150	OR 60 × 2.5 N		C1 A1	
	(iii) 750	N e.c.f. from (c) (i) 2 and/or (c) (ii)		B1	
	(iv) sam	ne as his (c) (i) 2 accept 600 N if no value given in (c)	(i) 2.	B1	
					[8]
5	(a) (P.E.) = 12 × 10 360 J			C1 C1 A1	
	(b) (P =) E/t 360/60 6 W	352.8 J gives 5.88 W 353.16 J gives 5.886 W (minir	num 2 s.f.)	C1 C1 A1	
					[6]
6	(a) (i) incr	eases		B1	
	1.05	= const in any form 5 (× 10 ⁵) × 860 (× 10 ⁻⁶) = p × 645 (× 10 ⁻⁶) × 10 ⁵ Pa		C1 C1 A1	

(iii) F = pA in any form accept weight for F	. a	ge o	IGCSE - October/November 2000	09118585	31	
EITHER increase in pressure = 0.35 × 10 ⁵ (Pa) C1 0.35 × 10 ⁵ × 50.4 10 ³ C1 175 N (minimum 2 s.f.) c.a.o. A1 OR 1.05 × 10 ⁵ × 5.0 × 10 ⁻³ or 525 N or 1.4 × 10 ⁵ × 5.0 × 10 ⁻³ or 700 N (C1) 700 – 525 N e.c.f. from (a) (ii) 175 N (minimum 2 s.f.) c.a.o. (A1) (b) (i) increases B1 (ii) no change B1 (iii) extra weight (on tray/piston) B1 (iv) increases B1 (b) galvanometer OR millivoltmeter OR milliammeter OR digital ammeter copper constantan copper B1 (c) rapid response small area can measure high / low temperatures small area can measure high / low temperatures small thermal capacity (idea of) any 1 remote reading large range data logging / continuous monitoring possible takes temperature of a surface N.B. (very) sensitive not accepted (b) any two standard rays correctly drawn (no extrapolation needed) B1 (b) any two standard rays correctly drawn (no extrapolation needed) B1 correct rays extrapolated back to intersect virtual image drawn at candidate's intersection of extrapolated rays (condone no I, if clear) B1			IGCSE – October/November 2009	0625	31	
OR 1.05 × 10° × 5.0 × 10° 3 or 525 N or 1.4 × 10° × 5.0 × 10° 3 or 700 N (C1) 700 – 525 N e.c.f. from (a) (iii) 175 N (minimum 2 s.f.) c.a.o. (b) (i) increases (ii) no change (iii) extra weight (on tray/piston) (iv) increases B1 (iv) increa	(` '	THER increase in pressure = 0.35×10^{5} (Pa $0.35 \times 10^{5} \times 5.0 \times 10^{-3}$	a)	C1 C1	
(iii) extra weight (on tray/piston) (iv) increases B1 (iv) increases B1 [12] 7 (a) EITHER OR copper constantan copper CR digital voltmeter (b) galvanometer OR millivoltmeter OR milliammeter OR digital ammeter OR digital voltmeter (c) rapid response		OF	R $1.05 \times 10^5 \times 5.0 \times 10^{-3}$ or 525 N or $1.4 \times 10^5 \times 5.0$ 700 – 525 N e.c.f. from (a) (ii)	0 × 10 ⁻³ or 700	N (C1) (C1)	
(iii) extra weight (on tray/piston) (iv) increases B1 (iv) increases B1 [12] 7 (a) EITHER OR copper constantan copper constantan copper constantan copper constantan (b) galvanometer OR millivoltmeter OR milliammeter OR digital ammeter OR digital voltmeter (c) rapid response small area can measure high / low temperatures small thermal capacity (idea of) any 1 any 1 and 1 large range data logging / continuous monitoring possible takes temperature of a surface N.B. (very) sensitive not accepted (a) 2 cm (by eye) vertical object somewhere between F ₂ and lens (condone no O, if clear) (b) any two standard rays correctly drawn (no extrapolation needed) any to the properties of the properties of extrapolated rays (condone no I, if clear) (b) any two standard rays correctly drawn (no extrapolated rays (condone no I, if clear) (c) rapid response small ammeter OR digital	(b)	(i) inc	reases		B1	
(iv) increases [12] 7 (a) EITHER OR copper constantan copper constantan copper constantan		(ii) no	change		B1	
7 (a) EITHER OR copper constantan copper constantan copper constantan copper constantan copper constantan copper B1 (b) galvanometer OR millivoltmeter OR milliammeter OR digital ammeter OR digital voltmeter B1 (c) rapid response small area) can measure high / low temperatures) small thermal capacity (idea of)) any 1 B1 remote reading) large range data logging / continuous monitoring possible) takes temperature of a surface) N.B. (very) sensitive not accepted (a) 2 cm (by eye) vertical object somewhere between F ₂ and lens (condone no O, if clear) B1 (b) any two standard rays correctly drawn (no extrapolation needed) B1 correct rays extrapolated back to intersect virtual image drawn at candidate's intersection of extrapolated rays (condone no I, if clear) B1	((iii) ext	tra weight (on tray/piston)		B1	
7 (a) EITHER OR copper constantan copper constantan copper constantan copper constantan copper constantan copper B1 (b) galvanometer OR millivoltmeter OR milliammeter OR digital ammeter OR digital voltmeter B1 (c) rapid response	((iv) inc	reases		B1	
copper constantan copper Constantan copper Constantan Copper Constantan Copper Constantan Copper Constantan Copper Copper Constantan Copper Copper Copper Constantan Copper Coppe						[12]
copper constantan copper B1 (b) galvanometer OR millivoltmeter OR milliammeter OR digital ammeter OR digital voltmeter B1 (c) rapid response small area can measure high / low temperatures small thermal capacity (idea of) any 1 B1 remote reading large range data logging / continuous monitoring possible takes temperature of a surface N.B. (very) sensitive not accepted (a) 2 cm (by eye) vertical object somewhere between F2 and lens (condone no O, if clear) B1 (b) any two standard rays correctly drawn (no extrapolation needed) B1 correct rays extrapolated back to intersect B1 virtual image drawn at candidate's intersection of extrapolated rays (condone no I, if clear) B1	7 (a)	EITHE	R OR			
(b) galvanometer OR millivoltmeter OR milliammeter OR digital ammeter OR digital voltmeter (c) rapid response						
(c) rapid response small area can measure high / low temperatures small thermal capacity (idea of) any 1 B1 remote reading large range data logging / continuous monitoring possible takes temperature of a surface N.B. (very) sensitive not accepted (a) 2 cm (by eye) vertical object somewhere between F ₂ and lens (condone no O, if clear) B1 (b) any two standard rays correctly drawn (no extrapolation needed) correct rays extrapolated back to intersect virtual image drawn at candidate's intersection of extrapolated rays (condone no I, if clear) B1					B1	
small area can measure high / low temperatures small thermal capacity (idea of) small thermal capac	(b)	•		<u>ital</u> ammeter	B1	
 (a) 2 cm (by eye) vertical object somewhere between F₂ and lens (condone no O, if clear) (b) any two standard rays correctly drawn (no extrapolation needed) correct rays extrapolated back to intersect birtuial image drawn at candidate's intersection of extrapolated rays (condone no I, if clear) 	(c)	small a can me small th remote large ra data log takes to	rea) easure high / low temperatures) hermal capacity (idea of)) any 1 reading) ange) gging / continuous monitoring possible) emperature of a surface)		B1	
(condone no O, if clear) (b) any two standard rays correctly drawn (no extrapolation needed) correct rays extrapolated back to intersect virtual image drawn at candidate's intersection of extrapolated rays (condone no I, if clear) B1						[3]
correct rays extrapolated <u>back</u> to intersect burning back to intersect virtual image drawn at candidate's intersection of extrapolated rays (condone no I, if clear) B1	8 (a)	2 cm (b		ar)	B1	
(condone no I, if clear) B1	(b)	correct	rays extrapolated back to intersect	•		
[4]		virtual i	·	ays	B1	
•						[4]

Mark Scheme: Teachers' version

Syllabus

Paper

Page 6

	Page 7		Mark Scheme: Teachers' version	Syllabus	Paper
			IGCSE – October/November 2009	0625	31
9) (quantity of) heat/energy to raise temp by 1 °C/1degC/1K/unit temp rise 1 kg OR 1 g OR unit mass (Mention of change of state gets M0 A0)			
	lon	g time ensiv	e to heat up/cook) e to cool down) any 1 ve to heat) lot of energy to heat up)		B1
	(c) (i)		degC OR 1.8 °C OR 1.8 K D 77.1 degC OR 77.1 °C OR 77.1K		B1
	(ii)	0.2	e) mcT in any form, seen anywhere × 4200 × 1.8 e.c.f. from (c) (i) 2 J (minimum 2 s.f.) c.a.o.		B1 C1 A1
	(iii)		$2 = 0.05 \times c \times 77.1$ in any form e.c.f. from (c) (i) and J/kg K (N.B. must be to 3 sf; A0 for wrong s.f.) e.c.f.	/or (c) (ii)	C1 A1
	(iv)	boili at 10 ener ther	t lost during transfer ing water not at 100 °C / reason for not boiling 00 °C e.g. water not pure/ not standard pressure rgy lost to cup etc. / surroundings mometer not accurate / sensitive enough perature / mass(es) not accurately measured)	any 1	B1
					[10]
10	(a) (i)	step	o-up transformer		В1
	(ii)		heat/energy/power loss (from lines) / thinner wires (po lower current NOT more efficient	ssible)	B1
	(b) P = 2.5		I in any form, figures or symbols / (P =) VI		C1 A1
			in any form, figures or symbols / (P =) I ² R e.c.f. from (b)		C1 A1
			in any form, figures or symbols OR (V =) IR OR R in any form, figures or symbols OR (P =) V² / R OR	$R V = (PR)^{1/2}$	C1
	7.5	V e.	c.f. from (b) or (c)		A1

Page 8		8	Mark Scheme: Teachers' version	Syllabus	Paper
			IGCSE – October/November 2009	0625	31
	21 OF 55	,985 ∨ R ,000 –	7.5 – 7.5 OR 22,000 – 7.5 ecf e.c.f. (minimum 4 s.f.in this case) 37.5 = 54962.5 / 2.5 = 21985 V (minimum 4 s.f. in this case)		C1 A1 (C1) (A1)
					[10]
11	(a) A B	NOT AND	or inverter		B1 B1
	(b) (ac	ccept 1	or ON for HIGH, and 0 or OFF or NOT HIGH for LOW	/ throughout)	
	(i)	A – I	HIGH and B – LOW (both) no e.c.f.		B1
	(ii)	A – I	HIGH and B – HIGH (both) no e.c.f.		B1
	(iii)	A – I	LOW and B – LOW (both) no e.c.f.		B1
	(c) (i)		nnot provide enough power / current for lamp, or equi allows remote lamp	V.	B1
	(ii)	the s	second one / dark and warm / HIGH, HIGH e.c.f. from	(b)	B1
	(iii)		ning if temperature in a closed / dark space (e.g. refrigenigh a value	erator, kiln) reach	es
			"to switch on a lamp when it is dark and warm" not ac	cepted	B1
					[8]